

## SAFETY DATA SHEET

### SECTION: 1 PRODUCT and COMPANY IDENTIFICATION

**Product Name:** HAND SANITIZER (all sizes)  
**Product Synonyms:** Hand Rub, Alcohol-Based Hand Rub, Alcohol-Based Hand Sanitizer, Sanitizer  
**Country of Origin:** USA  
**Product Use:** ALL PROPER AND LEGAL PURPOSES  
**Company:** Essential Depot, Inc.  
2029 US Hwy 27 S  
Sebring, Florida 33870  
**Phone:** 863-662-0481  
**Emergency Phone:** CHEMTREK, Inside the USA: 1-800-424-9300

### SECTION: 2. HAZARDS IDENTIFICATION

**Physical hazards:** Flammable liquids Category 2  
**Health hazards:** Serious eye damage/eye irritation Category 2A  
**Environmental hazards:** Not classified.  
**OSHA defined hazards:** Not classified.

**Label elements:**



Signal word: Danger  
Hazard statement: Highly flammable liquid and vapor. Causes serious eye irritation.  
Precautionary statement  
Prevention: Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Wash thoroughly after handling. Wear protective gloves/eye protection/face protection.  
Response: If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye

## SAFETY DATA SHEET

irritation persists: Get medical advice/attention. In case of fire: Use appropriate media to extinguish.

Storage:

Disposal:

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC):**

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

**Supplemental information:**

2.11% of the mixture consists of component(s) of unknown acute oral toxicity.  
76.1% of the mixture consists of component(s) of unknown acute dermal toxicity.  
99.82% of the mixture consists of component(s) of unknown acute inhalation toxicity.

### SECTION: 3. COMPOSITION / INFORMATION INGREDIENTS

**Mixtures:**

Chemical Name	Common name and synonyms	CAS #	%
Ethonal		64-17-5	73.9871
Hydrogen Peroxide (H2O2)		7722-81-1	0.1645
Methanol		67-56-1	0.0111
Acetaldehyde		75-07-0	0.0015
2-Propanone		67-64-1	0.0003
Other components below reportable levels			25.8355

### SECTION: 4. FIRST AID MEASURES

**Inhalation:**

Move to fresh air. Call a physician if symptoms develop or persist.

**Skin contact:**

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical attention if irritation develops and persists.

**Eye contact:**

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get

SAFETY DATA SHEET

	medical attention if irritation develops and persists.
<b>Ingestion:</b>	Rinse mouth. Get medical attention if symptoms occur.
<b>Most important symptoms/effects, acute and delayed:</b>	Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.
<b>Indication of immediate medical attention and special treatment needed:</b>	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.
<b>General information:</b>	Take off all contaminated clothing immediately. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

SECTION: 5. FIRE FIGHTING MEASURES

<b>Suitable extinguishing media:</b>	Water fog. Alcohol resistant foam. Carbon dioxide (CO <sub>2</sub> ). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
<b>Unsuitable extinguishing media:</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical:</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be

SAFETY DATA SHEET

**Special protective equipment and precautions for firefighters:**

worn in case of fire.

**Fire fighting equipment/instructions:**

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

**Specific methods:**

Use standard firefighting procedures and consider the hazards of other involved materials.

**General fire hazards:**

Highly flammable liquid and vapor.

SECTION: 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures:**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

SAFETY DATA SHEET

**Methods and materials for containment and cleaning up:**

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent entry into waterways, sewer, basements or confined areas.

**Large Spills:** Stop the flow of material if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

**Small Spills:** Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions**

Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

SECTION: 7. HANDLING AND STORAGE

**Precautions for safe handling:**

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Avoid contact with eyes. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

SAFETY DATA SHEET

**Conditions for safe storage, including any incompatibilities:**

Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

SECTION: 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

**Occupational exposure limits:**

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value
2-PROPANONE (CAS 67-64-1)	PEL	2400 mg/m <sup>3</sup> 1000ppm
ACETALDEHYDE(CAS 75-07-0)	PEL	360mg/m <sup>3</sup> 200ppm
ETHANOL (CAS 64-17-5)	PEL	1900mg/m <sup>3</sup> 1000ppm
HYDROGEN PEROXIDE (H <sub>2</sub> O <sub>2</sub> ) (CAS 7722-84-1)	PEL	1.4mg/m <sup>3</sup> 1ppm
METHANOL (CAS 67-56-1)	PEL	260mg/m <sup>3</sup> 200ppm

**US. ACGIH Threshold Limit Values**

Components	Type	Value
2-PROPANONE (CAS 67-64-1)	STEL TWA	500ppm 250ppm
ACETALDEHYDE(CAS 75-07-0)	Ceiling	25pp,
ETHANOL (CAS 64-17-5)	STEL	1000ppm
HYDROGEN PEROXIDE (H <sub>2</sub> O <sub>2</sub> ) (CAS 7722-84-1)	TWA	1ppm
METHANOL (CAS 67-56-1)	STEL TWA	250ppm 200ppm

## SAFETY DATA SHEET

### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
2-PROPANONE (CAS 67-64-1)	TWA	590mg/m3 250ppm
ETHANOL (CAS 64-17-5)	TWA	1000mg/m3 1000ppm
HYDROGEN PEROXIDE (H2O2) (CAS 7722-84-1)	TWA	1.4mg/m3 1ppm
METHANOL (CAS 67-56-1)	STEL	325mg/m3 250ppm
	TWA	260mg/m3 200ppm

### Biological limit values:

#### ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
2-PROPANONE (CAS 67-64-1)	25mg/l	Acetone	Urine	
METHANOL (CAS 67-56-1)	15mg/l	Methanol	Urine	

### Exposure guidelines:

#### US - California OELs: Skin designation

METHANOL (CAS 67-56-1)

Can be absorbed through the skin.

#### US - Minnesota Haz Subs: Skin designation applies

METHANOL (CAS 67-56-1)

Skin designation applies.

#### US - Tennessee OELs: Skin designation

METHANOL (CAS 67-56-1)

Can be absorbed through the skin.

#### US ACGIH Threshold Limit Values: Skin designation

METHANOL (CAS 67-56-1)

Can be absorbed through the skin.

#### US NIOSH Pocket Guide to Chemical Hazards: Skin designation

METHANOL (CAS 67-56-1)

Can be absorbed through the skin.

SAFETY DATA SHEET

<b>Appropriate engineering controls:</b>	Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.
<b>Individual protection measures, such as personal protective equipment:</b>	The following are recommendations for Personnel Protective Equipment (PPE). The employer/user of this product must perform a Hazard Assessment of the workplace according to OSHA regulations 29 CFR 1910.132 to determine the appropriate PPE for use while performing any task involving potential exposure to this product.
<b>Eye/face protection:</b>	Wear safety glasses with side shields (or goggles).
<b>Hand protection:</b>	Wear appropriate chemical resistant gloves.
<b>Other skin protection:</b>	Wear appropriate chemical resistant clothing.
<b>Respiratory protection:</b>	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.
<b>Thermal hazards:</b>	Wear appropriate thermal protective clothing, when necessary
<b>General hygiene considerations:</b>	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

SECTION: 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	
<b>Physical state:</b>	Liquid.
<b>Form:</b>	Liquid.
<b>Color:</b>	Colorless
<b>Odor:</b>	Alcohol
<b>Odor threshold:</b>	Not Available
<b>pH:</b>	Not Available



SAFETY DATA SHEET

<b>Melting point/freezing point:</b>	190.74 °F (88.19 °C) estimated
<b>Flash point:</b>	72.0 °F (22.2 °C)
<b>Evaporation rate:</b>	Not available
<b>Flammability (solid, gas):</b>	Not available
<b>Flammability limit-lower(%):</b>	Not available
<b>Flammability limit-upper(%):</b>	Not available
<b>Explosive limit-lower(%):</b>	Not available
<b>Explosive limit-upper(%):</b>	Not available
<b>Vapor pressure:</b>	Not available
<b>Vapor density:</b>	Not available
<b>Relative density:</b>	Not available
<b>Solubility (water):</b>	Not available
<b>Partition coefficient (n-octanol/water):</b>	Not available
<b>Auto-ignition temperature:</b>	Not available
<b>Decomposition temperature:</b>	Not available
<b>Viscosity:</b>	Not available
<b>Density:</b>	7.21 lbs/gal 0.86 g/ml
<b>Explosive properties:</b>	Not explosive
<b>Flammability class:</b>	Flammable 1B estimated
<b>Oxidizing properties:</b>	Not oxidizing
<b>Percent volatile:</b>	99.84% estimated
<b>Specific gravity:</b>	0.86
<b>VOC:</b>	76.11% estimated

SECTION: 10. STABILITY AND REACTIVITY

**Reactivity:** The product is stable and non-reactive under normal conditions of use,

SAFETY DATA SHEET

storage and transport.

**Chemical stability:** Material is stable under normal conditions.

**Possibility of hazardous reactions:** Hazardous polymerization does not occur.

**Conditions to avoid:** Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

**Incompatible materials:** Strong oxidizing agents.

**Hazardous decomposition products:** No hazardous decomposition products are known.

SECTION: 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

Inhalation: Prolonged inhalation may be harmful.

Skin contact: No adverse effects due to skin contact are expected.

Eye contact: Causes serious eye irritation.

Ingestion: Expected to be a low ingestion hazard.

**Symptoms related to the physical, chemical and toxicological characteristics:** Headache. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Coughing.

**Information on toxicological effects**

**Acute toxicity:** Not known.

Components	Species	Test Results
2-PROPANONE (CAS 67-64-1)		
<b>Acute Dermal</b> LD50	Rabbit	20000 mg/kg
<b>Oral</b> LD50	Rat	5800 mg/kg
ACETALDEHYDE (CAS 75-07-0)		
<b>Acute Dermal</b>		

SAFETY DATA SHEET

LD50 Rabbit 3540 mg/kg

Oral LD50 Rat 661 mg/kg

ETHANOL (CAS 64-17-5)

**Acute**

**Oral**

LD50 Rat 6.2 g/kg

METHANOL (CAS 67-56-1)

**Acute**

**Dermal**

LD50 Rabbit 15800 mg/kg

**Inhalation**

LD50 Cat 85.41 mg/l, 4.5 Hours  
 Rat 64000 ppm, 4 Hours  
 87.5 mg/l, 6 Hours

**Oral**

LD50 Dog 8000 mg/kg  
 Monkey 2 g/kg  
 Mouse 7300 mg/kg  
 Rabbit  
 Rat

**Skin corrosion/irritation:** Due to partial or complete lack of data the classification is not possible.

**Serious eye damage/eye irritation:** Causes serious eye irritation.

**Respiratory sensitization:** Due to partial or complete lack of data the classification is not possible.

**Skin sensitization:** Due to partial or complete lack of data the classification is not possible.

**Germ cell mutagenicity:** Due to partial or complete lack of data the classification is not possible.:

**Carcinogenicity:** Due to partial or complete lack of data the classification is not possible.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

ACETALDEHYDE (CAS 75-07-0) 2B Possibly carcinogenic to humans.  
 HYDROGEN PEROXIDE (H2O2) (CAS 7722-84-1) 3 Not classifiable as to carcinogenicity to humans.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)**

Not listed.

**US. National Toxicology Program (NTP) Report on Carcinogens**

ACETALDEHYDE (CAS 75-07-0) Reasonably Anticipated to be a Human Carcinogen.

## SAFETY DATA SHEET

<b>Reproductive toxicity:</b>	Possible reproductive hazard.
<b>Specific target organ toxicity - single exposure:</b>	Due to partial or complete lack of data the classification is not possible.
<b>Specific target organ toxicity - repeated exposure:</b>	Due to partial or complete lack of data the classification is not possible.
<b>Aspiration hazard:</b>	Due to partial or complete lack of data the classification is not possible.
<b>Chronic effects:</b>	Prolonged inhalation may be harmful.
<b>Further information:</b>	Acetone has increased the liver toxicity of chemicals, such as, carbon tetrachloride, chloroform and trichloroethylene. Acetone has also increased the lung toxicity of styrene and the toxicity of acrylonitrile and 2,5 hexanedione in laboratory animals. Acetone also appears to inhibit the metabolism and elimination of ethyl alcohol, thereby potentiating its toxicity. Acetone can increase or decrease the toxicity of 1,2-dichlorobenzene, depending on the concentration of Acetone.

## SECTION: 12. ECOLOGICAL INFORMATION

**Ecotoxicity:** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
2-PROPANONE (CAS 67-64-1) <b>Aquatic</b> Crustacea Fish	EC50 LC50	Water flea (Daphnia magna) Rainbow trout, Donaldson trout (Oncorhynchus mykiss)
10294 – 17704 mg/l, 48 hours 4740 – 6330 mg/l, 96 hours		
ACETALDEHYDE (CAS 75-07-0) <b>Aquatic</b> Crustacea Fish	EC50 LC50	Water flea (Daphnia magna) Fathead minnow (Pimephales promelas)
39.4 – 59.1 mg/l, 48 hours 28 – 34 mg/l, 96 hours		
ETHANOL (CAS 64-17-5) <b>Aquatic</b> Crustacea Fish	EC50 LC50	Water flea (Daphnia magna) Fathead minnow (Pimephales promelas)
7.7 – 11.2 mg/l, 48 hours > 100 mg/l, 96 hours		
METHANOL (CAS 67-56-1) <b>Aquatic</b> Crustacea Fish	EC50 LC50	Water flea (Daphnia magna) Fathead minnow (Pimephales promelas)
> 10000 mg/l, 48 hours > 100 mg/l, 96 hours		

**Bioaccumulative potential:**

SAFETY DATA SHEET

**Partition coefficient n-octanol / water (log Kow)**

2-PROPANONE	-0.24
ETHANOL	-0.31
METHANOL	-0.77

**Mobility in soil:** No data available

**Other adverse effects:** The product contains volatile organic compounds which have a photochemical ozone creation potential.

SECTION: 13. DISPOSAL CONSIDERATION

**Disposal instructions:** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations:** Dispose in accordance with all applicable regulations.

**Hazardous waste code:** D001: Waste Flammable material with a flash point <140 F  
The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues/unused products:** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging:** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION: 14. TRANSPORT INFORMATION

**UN number:** UN1170

SAFETY DATA SHEET

**UN proper shipping name:** ETHANOL SOLUTIONS  
**Transport hazard class(es):** Class: 3  
Subsidiary risk:  
**Packing Group:** II  
**Special precautions for user:** Read safety instructions, SDS and emergency procedures before handling.  
**ERG number:** 127

Transportation information on packaging may be different from that listed.



**General information:** IMDG Regulated Marine Pollutant.

SECTION: 15. REGULATORY INFORMATION

**US federal regulations:** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**Toxic Substances Control Act (TSCA)**

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

ACETALDEHYDE (CAS 75-07-0) 0.1 % One-Time Export Notification only.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

2-PROPANONE (CAS 67-64-1) Listed.

ACETALDEHYDE (CAS 75-07-0) Listed.

METHANOL (CAS 67-56-1) Listed.

**SARA 304 Emergency release notification**

HYDROGEN PEROXIDE (CONC.> 52%) 1000 LBS  
(CAS 7722-84-1)

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)**

Not Listed.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**SARA 302 Extremely hazardous substance**

## SAFETY DATA SHEET

Chemical name	CAS #	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
HYDROGEN PEROXIDE (H2O2)	7722-84-1	1000	1000		

**SARA 311/312 Hazardous** Yes

**Classified hazard categories:** Flammable (gases, aerosols, liquids, or solids) Serious eye damage or eye irritation  
 Hazard not otherwise classified (HNOC)

**SARA 313 (TRI reporting):** Not regulated

### Other federal regulations

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

ACETALDEHYDE (CAS 75-07-0)

METHANOL (CAS 67-56-1)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

ACETALDEHYDE (CAS 75-07-0)

**Safe Drinking Water Act (SDWA)**

Contains component(s) regulated under the Safe Drinking Water Act.

**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

2-PROPANONE (CAS 67-64-1) 6532

**Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))**

2-PROPANONE (CAS 67-64-1) 35 % WV

**DEA Exempt Chemical Mixtures Code Number**

2-PROPANONE (CAS 67-64-1) 6532

**FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace**

2-PROPANONE (CAS 67-64-1) Low priority

ACETALDEHYDE (CAS 75-07-0) High priority

ETHANOL (CAS 64-17-5) Low priority

### US state regulations

**California Proposition 65**

## SAFETY DATA SHEET

**WARNING:** This product can expose you to ACETALDEHYDE, which is known to the State of California to cause cancer, and METHANOL, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**California Proposition 65 - CRT: Listed date/Carcinogenic substance**

ACETALDEHYDE (CAS 75-07-0) Listed: April 1, 1988

**California Proposition 65 - CRT: Listed date/Developmental toxin**

METHANOL (CAS 67-56-1) Listed: March 16, 2012

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

2-PROPANONE (CAS 67-64-1)  
 ACETALDEHYDE (CAS 75-07-0)  
 METHANOL (CAS 67-56-1)

**International Inventories:**

Country(s) or Region	Inventory name	On inventory (yes/no)
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

'A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

SECTION: 16. OTHER INFORMATION

**Creation Date:** April 09, 2020  
**Revision Date:** Nov 13, 2020



SAFETY DATA SHEET

**HMIS® ratings**

Health: 2  
Flammability: 3  
Physical hazard: 0

**NFPA ratings**

Health: 2  
Flammability: 3  
Instability: 0

**DISCLAIMER:**

The information contained in this Certificate of Analysis and Safety Data Sheet is obtained from current and reliable sources. The information contained herein is true and to the best of ESSENTIAL DEPOT Inc. knowledge. Nothing herein should be interpreted as a recommendation to infringe existing patents or violate any Laws or Regulation. Final determination of the suitability of the material is the sole responsibility of the user. Customers should purchase products from ESSENTIAL DEPOT Inc. with the clear understanding that all products must be used at the customers own discretion and only after referencing Safety Data Sheets (SDS) and all other relevant technical information specific to the product. ESSENTIAL DEPOT Inc. shall not be held responsible for any damages to property or for any adverse physical effects (including injury or bodily harm) caused by insufficient knowledge or the improper use of a product. The user of the product is solely responsible for compliance with all laws and regulations applying to the use of The products, including intellectual property rights of third parties. As with any manufacturing process, ESSENTIAL DEPOT Inc. strongly recommends small lab scale testing for evaluation purposes prior to full commercial manufacturing. The information on the ESSENTIAL DEPOT Inc. website is obtained from current and reliable sources but makes no representation as to its comprehensiveness or accuracy. Nothing contained herein should be considered as a recommendation by ESSENTIAL DEPOT Inc. as to the fitness for any use. As the ordinary or otherwise use(s) of this product is outside the control of ESSENTIAL DEPOT Inc., no representation or warranty, expressed or implied is made as to the effect(s) of such use(s) (including damage or injury), or the results obtained. The liability of ESSENTIAL DEPOT Inc. is limited to the value of the goods and does not include any consequential loss. ESSENTIAL DEPOT Inc. shall not be liable for any errors or delays in the content, or for any actions taken in reliance thereon.